
Centennial™



Centennial™ Specifications

Payroll/Attendance Recorder

The Centennial Time Recorder is a fully electronic, fully automatic payroll/attendance recorder. It is ideal for fixed-shift applications, because its auto-positioning and rapid punching can speed a line of employees in or out. In addition, with easy-to-program exception printing, only cards with highlighted exceptions need to be calculated.

Durable construction and quartz crystal accuracy assures reliable service in the most demanding environments. The built-in perpetual calendar eliminates resetting at the end of the month. Optional 72-hour power reserve ensures uninterrupted service, regardless of power failures.

Use one of Simplex's many standard cards, or let us print your own custom card. Either way, the Centennial Time Recorder will give you consistently clear, legible, permanent payroll/attendance records.

Features:

- Easily handles 200 employees, with up to 50 employees per shift
- Large easy-to-read liquid crystal time display
- Programmable 2-color printing to highlight exceptions punches
- Heavy-duty high-impact thermoplastic cover
- 12-or 24-hour time display and printing format
- Automatic Spring and Fall Daylight Saving Time changes
- Adjustable card receiver and print positioning to accept any time card format
- Bell ringing capability for up to 60 bell events per day
- Easy-to-change cartridge print ribbon
- Internal lithium battery protects against memory loss during power outages

Optional Features:

- Rechargeable Power Reserve Battery – allows full operation, even during power failures
- Signal Control (bell ringer) Relay – insures prompt starting and stopping of work activities by ringing a bell or horn at your scheduled times
- Master Clock Interface – permits Centennial's time keeping to be controlled by a Simplex Master Time Control System insuring time synchronization throughout your facility

Specifications:

- Color: Gray
- Dimensions: 15 1/2" x 12 1/2" x 8 1/2"
- Construction: Case and inner molding, injection molded high-impact thermoplastic
- Power Requirements: 120 volts AC, 60 Hz, 1 amp (also available for 220 volt AC, 50 or 60 Hz operation)
- Operating Environment: 32° to 122° F, 95% relative humidity, non-condensing
- Storage Environment: -10° to 140° F
- Shipping Weight: 18.2 lbs.
- Listing: Underwriters' Laboratories, Canadian Standards Association, VDE

Ordering Information:

- 1403-9110 Centennial 120v/60Hz
- 1403-9220 Centennial 220v/50Hz
- 1403-9801 Rechargeable Battery
- 1403-9802 Signal Control (bell ringer) Relay
- 1403-9803 Master Clock Interface



U.S.A.: Simplex Plaza • Gardner, MA 01441-0001 • Telephone (508) 632-2500, 1-800-225-0496

CANADA: 6300 Viscount Road • Mississauga, Ontario L4V 1H3 • Telephone 1-800-565-5400

AUSTRALIA: 140 Old Pittwater Road • Brookvale, NSW 2100 • Telephone (61) 131 491

HONG KONG: Suites 1-6, 20/F, Tower II, Enterprise Square, 9 Sheung Yuet Road
• Kowloon Bay, Kowloon • Telephone (852) 2796-6163



U.S.A.: Simplex Plaza • Gardner, MA 01441-0001 • Telephone (508) 632-2500, 1-800-225-0496
CANADA: 6300 Viscount Road • Mississauga, Ontario L4V 1H3 • Telephone 1-800-565-5400
AUSTRALIA: 140 Old Pittwater Road • Brookvale, NSW 2100 • Telephone (61) 131 491
HONG KONG: Suites 1-6, 20/F, Tower II, Enterprise Square, 9 Sheung Yuet Road
 • Kowloon Bay, Kowloon • Telephone (852) 2796-6163